## NSN 6110-01-155-9446

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-155-9446

| One LA Production   |
|---|
| Speed Adjustments:  |
| Two speed   |
| Hazardous Locations/environmental Protection:   |
| Dripproof   |
| Overall Length:   |
| 22.109 inches   |
| Overall Height:   |
| 9.500 inches  |
| Overall Width:  |
| 17.109 inches   |
| Ac Voltage Rating:  |
| 440.0 volts   |
| Frequency Rating:   |
| 60.0 hertz  |
| Actuation Method:   |
| Magnetic  |
| Performance Type:   |
| Manual  |
| Fuse Accommodation Quantity:  |
| 6   |
| Size Designator:  |
| 2/1   |
| Duty Cycle:   |
| Continuous  |
| Mounting Configuration:   |
| Four 17/32 in. Diameter holes; rectangular pattern; on 13-1/2 in. By 20-3/8 in. Centers |
| Operating Voltage Characteristic:   |
| Full  |
| Horsepower Rating:  |
| 25.000  |
| Actuator Voltage:   |
| 440.0 ac  |
| Fuse Current Rating In Amps:  |
| 10.0  |
| Load Protection Type:   |
| Overload and undervoltage   |
| Ambient Temp:   |
| 50.0 degrees celsius  |
| Inclosure Feature:  |
| Dripproof   |
| National Electrical Manufacturers Association Standards Design:                         |

Designed per nema std

## NSN 6110-01-155-9446

Motor Controller - Page 2 of 2



| Switch Functional Positions:                       |
|--|
| Emergency run and fast and reset and slow and stop |
| Control Type:                                      |
| Local  |
| Features Provided:                                 |
| Circuit protection fuse                            |
| Phase:   |
| Three  |
| Frequency In Hertz:                                |
| 60.0   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                   |
|  |
| Demilitarization:                                  |
| No   |
| Fiig:  |
| A541b0   |

Mil-std (military Standard):

Mil-c-2212 spec.