# NSN 6110-01-157-4412

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-157-4412

# Speed Adjustments:

0 to full speed

# Hazardous Locations/environmental Protection:

Dripproof

# **Overall Length:**

19.125 inches

### **Overall Height:**

8.562 inches

#### **Overall Width:**

14.125 inches

#### Ac Voltage Rating:

440.0 volts

#### Frequency Rating:

60.0 hertz

#### **Actuation Method:**

Actuation

# Magnetic

# Performance Type:

Manual

### **Fuse Accommodation Quantity:**

4

# Size Designator:

2

### Duty Cycle:

Continuous

### **Mounting Configuration:**

Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 17-3/8 in. Centers

### **Operating Voltage Characteristic:**

Full

#### Horsepower Rating:

25.000

#### Actuator Voltage:

440.0 ac

#### **Fuse Current Rating In Amps:**

10.0

#### Load Protection Type:

Overload and undervoltage

# Ambient Temp:

50.0 degrees celsius

# **Inclosure Feature:**

Dripproof

#### National Electrical Manufacturers Association Standards Design:

Designed per nema std

# NSN 6110-01-157-4412

Motor Starter - Page 2 of 2



**Switch Functional Positions:** 

Emergency run and reset and start and stop

Control Type:

Local

Features Provided:

Circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0

Mil-std (military Standard):

Mil-c-2212 spec.