NSN 6110-01-158-0485

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-158-0485

| Speed Adjustments: |
|---|
| 0 to full speed |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 19.125 inches |
| Overall Height: |
| 7.562 inches |
| Overall Width: |
| 14.421 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Performance Type: |
| Manual |
| Fuse Accommodation Quantity: |
| 4 |
| Size Designator: |
| 0 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 17-3/8 in. Centers |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 5.000 |
| Actuator Voltage: |
| 440.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 |
| Load Protection Type: |
| Overload and undervoltage |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |

Designed per nema std

NSN 6110-01-158-0485

Motor Starter - Page 2 of 2



Switch Functional Positions: Emergency run and off and reset and run and standby and start **Control Type:** Local **Features Provided:** Circuit protection fuse Phase: Three **Special Features:** Run; stand by; off provided by selector switch Frequency In Hertz: 60.0 Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A541c0

Mil-c-2212 spec.

Mil-std (military Standard):