NSN 6110-01-159-3688

Motor Starter - Page 1 of 2

Three



View Online at https://aerobasegroup.com/nsn/6110-01-159-3688

| Hazardous Locations/environmental Protection: |
|---|
| Dripproof |
| Overall Length: |
| 15.125 inches |
| Overall Height: |
| 8.562 inches |
| Overall Width: |
| 14.125 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Manual |
| Performance Type: |
| Manual |
| Fuse Accommodation Quantity: |
| 4 |
| Size Designator: |
| 0 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 13-3/8 in. Centers |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 5.000 |
| Fuse Current Rating In Amps: |
| 10.0 |
| Ambient Temp: |
| 50.0 degrees celsius |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Switch Functional Positions: |
| Emergency run and reset and run and stop |
| Control Type: |
| Local |
| Features Provided: |
| Circuit protection fuse |
| Phase: |

NSN 6110-01-159-3688

Motor Starter - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

Fiig:

A541c0

Shelf Life:

Mil-std (military Standard):

Mil-c-2212 spec.