Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-161-3694 Hazardous Locations/environmental Protection: Dripproof Overall Length: 17.187 inches Overall Height: 8.437 inches Overall Width: 14.500 inches Ac Voltage Rating: 440.0 volts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Manual Fuse Accommodation Quantity: 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Motor Starter - Page 1 of 2
DripproofOverall Length:17.187 inchesOverall Height:8.437 inchesOverall Width:14.500 inchesAc Voltage Rating:440.0 voltsFrequency Rating:60.0 hertzActuation Method:MagneticPerformance Type:ManualFuse Accommodation Quantity:4Size Designator:1Duty Cycle:ContinuousMounting Configuration:Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. CentersOperating Voltage Characteristic:FullActuator Voltage:40.0 acFuse Current Rating In Amps:10.0Ambient Temp:	View Online at https://aerobasegroup.com/nsn/6110-01-161-3694
Overall Length:17.187 inchesOverall Height:8.437 inchesOverall Width:14.500 inchesAc Voltage Rating:440.0 voltsFrequency Rating:60.0 hertzActuation Method:MagneticPerformance Type:ManualFuse Accommodation Quantity:4Size Designator:1Duty Cycle:ContinuousMounting Configuration:Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. CentersOperating Voltage Characteristic:FullActuator Voltage:440.0 acFuse Current Rating In Amps:10.0Ambient Temp:	Hazardous Locations/environmental Protection:
17.187 inchesOverall Height:8.437 inchesOverall Width:14.500 inchesAc Voltage Rating:440.0 voltsFrequency Rating:60.0 hertzActuation Method:MagneticPerformance Type:ManualFuse Accommodation Quantity:4Size Designator:1Duty Cycle:ContinuousMounting Configuration:Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. CentersOperating Voltage Characteristic:Fuil440.0 acFuse Current Rating In Amps:1.0Ambient Temp:	Dripproof
Overall Height:8.437 inchesOverall Width:14.500 inchesAc Voltage Rating:440.0 voltsFrequency Rating:60.0 hertzActuation Method:MagneticPerformance Type:ManualFuse Accommodation Quantity:4Size Designator:1Duty Cycle:ContinuousMounting Configuration:Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. CentersOperating Voltage Characteristic:Full440.0 acFuse Current Rating In Amps:1.0Ambient Temp:	Overall Length:
 8.437 inches Overall Width: 14.500 inches Ac Voltage Rating: 440.0 volts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Manual Fuse Accommodation Quantity: 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp: 	17.187 inches
Overall Width:14.500 inchesAc Voltage Rating:440.0 voltsFrequency Rating:60.0 hertzActuation Method:MagneticPerformance Type:ManualFuse Accommodation Quantity:4Size Designator:1Duty Cycle:ContinuousMounting Configuration:Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. CentersOperating Voltage Characteristic:Fuil440.0 acFuse Current Rating In Amps:10.0Ambient Temp:	Overall Height:
14.500 inchesAc Voltage Rating:440.0 voltsFrequency Rating:60.0 hertzActuation Method:MagneticPerformance Type:ManualFuse Accommodation Quantity:4Size Designator:1Duty Cycle:ContinuousMounting Configuration:Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. CentersOperating Voltage Characteristic:Fuil440.0 acFuse Current Rating In Amps:10.0Ambient Temp:	8.437 inches
Ac Voltage Rating: 440.0 volts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Manual Fuse Accommodation Quantity: 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Overall Width:
440.0 volts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Manual Fuse Accommodation Quantity: 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	14.500 inches
Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Manual Fuse Accommodation Quantity: 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Ac Voltage Rating:
60.0 hertz Actuation Method: Magnetic Performance Type: Manual Fuse Accommodation Quantity: 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	440.0 volts
Actuation Method:MagneticPerformance Type:ManualFuse Accommodation Quantity:4Size Designator:1Duty Cycle:ContinuousMounting Configuration:Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. CentersOperating Voltage Characteristic:FullActuator Voltage:440.0 acFuse Current Rating In Amps:10.0Ambient Temp:	Frequency Rating:
Magnetic Performance Type: Manual Fuse Accommodation Quantity: 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	60.0 hertz
Performance Type: Manual Fuse Accommodation Quantity: 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Actuation Method:
Manual Fuse Accommodation Quantity: 4 Size Designator: 1 J Outy Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Magnetic
Fuse Accommodation Quantity: 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Performance Type:
 4 Size Designator: 1 Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Mibient Temp: 	Manual
Size Designator: 1 J Duty Cycle: Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Fuse Accommodation Quantity:
1Duty Cycle:ContinuousMounting Configuration:Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. CentersOperating Voltage Characteristic:FullActuator Voltage:440.0 acFuse Current Rating In Amps:10.0Ambient Temp:	4
Duty Cycle:ContinuousMounting Configuration:Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. CentersOperating Voltage Characteristic:FullActuator Voltage:440.0 acFuse Current Rating In Amps:10.0Ambient Temp:	Size Designator:
Continuous Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	1
 Mounting Configuration: Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp: 	Duty Cycle:
 Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp: 	Continuous
Operating Voltage Characteristic: Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Mounting Configuration:
Full Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Four 9/16 in. Diameter holes; rectangular pattern; on 11-1/2 in. By 15-3/8 in. Centers
Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Operating Voltage Characteristic:
440.0 ac Fuse Current Rating In Amps: 10.0 Ambient Temp:	Full
Fuse Current Rating In Amps: 10.0 Ambient Temp:	Actuator Voltage:
10.0 Ambient Temp:	440.0 ac
Ambient Temp:	Fuse Current Rating In Amps:
-	10.0
	Ambient Temp:
50.0 degrees celsius	50.0 degrees celsius

Inclosure Feature:

Dripproof

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Amp Size Rating:

27.0

Control Type:

Local

Features Provided:

Circuit protection fuse

NSN 6110-01-161-3694

Motor Starter - Page 2 of 2

Phase:

Three

Frequency In Hertz:

440.0

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A541c0

