## NSN 6110-01-162-8028

Motor Controller - Page 1 of 2

Local



View Online at https://aerobasegroup.com/nsn/6110-01-162-8028

| On and Adhistments  |
|---|
| Speed Adjustments:  |
| 0 to full speed   |
| Hazardous Locations/environmental Protection:                                     |
| Dripproof   |
| Overall Length:   |
| 26.120 inches   |
| Overall Height:   |
| 9.880 inches  |
| Overall Width:  |
| 18.100 inches   |
| Ac Voltage Rating:  |
| 440.0 volts   |
| Frequency Rating:   |
| 60.0 hertz  |
| Actuation Method:   |
| Magnetic  |
| Performance Type:   |
| Manual  |
| Fuse Accommodation Quantity:  |
| 1 and 2   |
| Size Designator:  |
| 2   |
| Duty Cycle:   |
| Continuous  |
| Mounting Configuration:   |
| Six 17/32 in. Diameter holes; rectangular pattern; on 7-1/4 in. By 24 in. Centers |
| Operating Voltage Characteristic:   |
| Full  |
| Horsepower Rating:  |
| 25.000  |
| Actuator Voltage:   |
| 440.0 ac  |
| Fuse Current Rating In Amps:  |
| 3.0 and 10.0  |
| Ambient Temp:   |
| 50.0 degrees celsius  |
| National Electrical Manufacturers Association Standards Design:                   |
| Designed per nema std   |
| Switch Functional Positions:  |
| Fast and slow and stop  |
| Control Type:   |
| ••  |

## NSN 6110-01-162-8028

Motor Controller - Page 2 of 2



| Features Provided:      |
|-------------------------|
| Circuit protection fuse |
| Phase:                  |
| Three                   |
| Frequency In Hertz:     |
| 60.0                    |
| Shelf Life:             |
| N/a                     |
| Unit Of Measure:        |
|                         |
| Demilitarization:       |
| No                      |
| Fiig:                   |
| A541b0                  |

Mil-std (military Standard):

Mil-c-2212 spec.