## NSN 6110-01-163-6936

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-163-6936

Speed Adjustments:
0 to full speed
Hazardous Locations/environmental Protection:
Dripproof  Overall Longths
Overall Length:
34.125 inches
Overall Height:
11.500 inches
Overall Width:
28.109 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Automatic and manual
Fuse Accommodation Quantity:
3
Size Designator:
1
Duty Cycle:
Continuous
Mounting Configuration:
Two rows of 4 ea 21/32 in. Diameter holes; 32 in. Between cl of rows; holes space 8-1/4, 8, and 8-1/4 in. C to c along cl of rows
Operating Voltage Characteristic:
Full
Horsepower Rating:
10.000
Actuator Voltage:
115.0 ac
Fuse Current Rating In Amps:
10.0
Load Protection Type:
Overload and undervoltage
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:
Dripproof
National Electrical Manufacturers Association Standards Design:

Designed per nema std

## **NSN 6110-01-163-6936** Motor Starter - Page 2 of 2



<b>Switch Functional Positions:</b>
Start and stop
Control Type:
Local
Features Provided:
Circuit protection fuse
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A541c0