NSN 6110-01-164-3720

Motor Starter - Page 1 of 2

50.0 degrees celsius



View Online at https://aerobasegroup.com/nsn/6110-01-164-3720

Speed Adjustments
Speed Adjustments:
0 to full speed
Hazardous Locations/environmental Protection:
Dripproof Overall Languida.
Overall Length:
20.390 inches
Overall Height:
13.000 inches
Overall Width:
51.375 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Automatic and manual
Fuse Accommodation Quantity:
2 and 2
Size Designator:
4
Duty Cycle:
Continuous
Mounting Configuration:
Eight 21/32 in. Diameter holes; rectangular pattern; two horizontal rows of 4 ea; 18-3/8 in. Cl to cl of rows; c to c spacing of holes from
right; 12-1/4 in.; 13-3/8 in.; 21 in.
Operating Voltage Characteristic:
Reduced
Voltage Reduction Method:
Autotransformer
Full Voltage Restoring Method:
Time limit acceleration
Horsepower Rating:
100.000
Actuator Voltage:
115.0 ac
Fuse Current Rating In Amps:
3.0 and 10.0
Load Protection Type:
Overload
Ambient Temp:

NSN 6110-01-164-3720 Motor Starter - Page 2 of 2



Inclosure Feature:
Dripproof
National Electrical Manufacturers Association Standards Design:
Designed per nema std
Switch Functional Positions:
Run and start
Control Type:
Local
Features Provided:
Circuit protection fuse
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A541c0