## NSN 6110-01-165-8949

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-165-8949

Speed Adjustments:
0 to full speed
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
18.120 inches
Overall Height:
10.380 inches
Overall Width:
14.100 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Manual
Fuse Accommodation Quantity:
3
Size Designator:
1
Duty Cycle:
Daily Gyolo.
Continuous
Continuous
Continuous  Mounting Configuration:
Continuous  Mounting Configuration:  Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers
Continuous  Mounting Configuration:  Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic:
Continuous  Mounting Configuration:  Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic:  Full
Continuous  Mounting Configuration:  Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic:  Full  Horsepower Rating:
Continuous  Mounting Configuration:  Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic:  Full  Horsepower Rating:  10.000
Continuous  Mounting Configuration:  Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic:  Full  Horsepower Rating:  10.000  Actuator Voltage:
Continuous  Mounting Configuration:  Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic:  Full  Horsepower Rating:  10.000  Actuator Voltage:  440.0 ac
Continuous  Mounting Configuration: Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic: Full  Horsepower Rating: 10.000  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps:
Continuous  Mounting Configuration: Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic: Full  Horsepower Rating: 10.000  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0
Continuous  Mounting Configuration: Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic: Full  Horsepower Rating: 10.000  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0  Load Protection Type:
Continuous  Mounting Configuration:  Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers  Operating Voltage Characteristic:  Full  Horsepower Rating: 10.000  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0  Load Protection Type:  Overload
Mounting Configuration: Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 16 in. Centers Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type: Overload Ambient Temp:

**Switch Functional Positions:** 

Emergency run and forward and off and on and reverse

## NSN 6110-01-165-8949

Motor Controller - Page 2 of 2



Control Type:
Local
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A541b0