NSN 6110-01-166-3851

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-166-3851

Two speed Hazardous Locations/environmental Protection: Dripproof Overall Length: 22.120 inches Overall Height: 9.380 inches Overall Width: 16.100 inches Ac Voltage Rating: 440.0 volts Frequency Rating: 60.0 hertz
Dripproof Overall Length: 22.120 inches Overall Height: 9.380 inches Overall Width: 16.100 inches Ac Voltage Rating: 440.0 volts Frequency Rating:
Overall Length: 22.120 inches Overall Height: 9.380 inches Overall Width: 16.100 inches Ac Voltage Rating: 440.0 volts Frequency Rating:
22.120 inches Overall Height: 9.380 inches Overall Width: 16.100 inches Ac Voltage Rating: 440.0 volts Frequency Rating:
Overall Height: 9.380 inches Overall Width: 16.100 inches Ac Voltage Rating: 440.0 volts Frequency Rating:
9.380 inches Overall Width: 16.100 inches Ac Voltage Rating: 440.0 volts Frequency Rating:
Overall Width: 16.100 inches Ac Voltage Rating: 440.0 volts Frequency Rating:
16.100 inches Ac Voltage Rating: 440.0 volts Frequency Rating:
Ac Voltage Rating: 440.0 volts Frequency Rating:
440.0 volts Frequency Rating:
Frequency Rating:
60.0 hertz
00.0 1101.2
Actuation Method:
Magnetic
Performance Type:
Manual
Fuse Accommodation Quantity:
6
Size Designator:
2/1
Duty Cycle:
Continuous
Mounting Configuration:
Four 17/32 in. Diameter holes; rectangular pattern; on 12-1/2 in. By 20 in. Centers
Operating Voltage Characteristic:
Full
Horsepower Rating:
25.000
Actuator Voltage:
440.0 ac
Fuse Current Rating In Amps:
10.0
Load Protection Type:
Overload
Ambient Temp:
50.0 degrees celsius
National Electrical Manufacturers Association Standards Design:
Designed per nema std

Switch Functional Positions:

Emergency run and fast and slow and start and stop

NSN 6110-01-166-3851

Motor Controller - Page 2 of 2



Control Type:
Local
Features Provided:
Circuit protection fuse
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A541b0

Mil-std (military Standard):

Mil-c-2212 spec.