# NSN 6110-01-166-5065

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-166-5065

# Speed Adjustments:

0 to full speed

### Hazardous Locations/environmental Protection:

Dripproof

# **Overall Length:**

24.125 inches

#### **Overall Height:**

9.875 inches

#### **Overall Width:**

16.109 inches

#### Ac Voltage Rating:

440.0 volts

#### Frequency Rating:

60.0 hertz

#### **Actuation Method:**

Magnetic

# Performance Type:

Automatic and manual

# **Fuse Accommodation Quantity:**

4

#### Size Designator:

1

#### Duty Cycle:

Continuous

#### Mounting Configuration:

Four 17/32 in. Diameter holes; rectangular pattern; on 12-1/2 in. By 20 in. Centers

#### **Operating Voltage Characteristic:**

Full

#### Horsepower Rating:

10.000

#### Actuator Voltage:

440.0 ac

#### **Fuse Current Rating In Amps:**

10.0

# Load Protection Type:

Overload and undervoltage

# Ambient Temp:

50.0 degrees celsius

# Inclosure Feature:

Dripproof

# National Electrical Manufacturers Association Standards Design:

Designed per nema std

# NSN 6110-01-166-5065

Motor Starter - Page 2 of 2



# **Switch Functional Positions:**

Automatic and emergency run and manual and reset and stop

Control Type:

Local

# Features Provided:

Circuit protection fuse

Phase:

Three

# **Special Features:**

Potential transformer for 110v control circuit

# Frequency In Hertz:

60.0

# Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

# Fiig:

A541c0

#### Mil-std (military Standard):

Mil-c-2212 spec.