NSN 6110-01-166-6592

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-166-6592

Speed Adjustments
Speed Adjustments:
0 to full speed
Hazardous Locations/environmental Protection:
Dripproof Overall Length:
Overall Length:
22.125 inches
Overall Height:
9.875 inches
Overall Width:
16.109 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
End Application:
Sperry corporation model an/ssq-8 (v)
Performance Type:
Semiautomatic
Fuse Accommodation Quantity:
4
Size Designator:
1
Duty Cycle:
Continuous
Mounting Configuration:
Four 17/32 in. Diameter holes; rectangular pattern; on 12-1/2 in. By 20 in. Centers
Operating Voltage Characteristic:
Full
Horsepower Rating:
10.000
Actuator Voltage:
440.0 ac
Fuse Current Rating In Amps:
10.0
Load Protection Type:
Overload and undervoltage
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:

Dripproof

NSN 6110-01-166-6592

Motor Starter - Page 2 of 2

A541c0



National Electrical Manufacturers Association Standards Design:
Designed per nema std
Switch Functional Positions:
Emergency run and reset and start and stop
Control Type:
Local
Features Provided:
Circuit protection fuse
Phase:
Three
Special Features:
Potential transformer for 110v control circuit
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: