NSN 6110-01-168-1620

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-168-1620

| Speed Adjustments: |
|----------------------------------------------------------------------------------------------------------------------------------|
| Single speed |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 38.000 inches |
| Overall Height: |
| 12.000 inches |
| Overall Width: |
| 30.000 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Performance Type: |
| Manual |
| Fuse Accommodation Quantity: |
| 2 and 4 |
| Size Designator: |
| 5/1 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Eight 15/32 in. Diameter holes; 4 spaced rectangular pattern 34 in. By 28-1/2 in.; 1 ea at midpoint of rectangular pattern sides |
| Operating Voltage Characteristic: |
| Full |
| Actuator Voltage: |
| 440.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 and 20.0 |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Amp Size Rating: |
| 270.0 and 27.0 |
| Switch Functional Positions: |
| Start and stop |

NSN 6110-01-168-1620

Motor Controller - Page 2 of 2



| Control Type: |
|------------------------------------------------------|
| Local |
| Features Provided: |
| Reversible and circuit protection fuse |
| Phase: |
| Three |
| Special Features: |
| Additional switch positions: inhaul, outhaul, stream |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A541b0