# NSN 6110-01-168-1620

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-168-1620

## **Speed Adjustments:**

Single speed

### Hazardous Locations/environmental Protection:

Dripproof

### **Overall Length:**

38.000 inches

#### **Overall Height:**

12.000 inches

#### **Overall Width:**

30.000 inches

#### Ac Voltage Rating:

440.0 volts

#### **Frequency Rating:**

60.0 hertz

#### **Actuation Method:**

# Magnetic

Performance Type:

#### Manual

**Fuse Accommodation Quantity:** 

2 and 4

#### Size Designator:

5/1

#### **Duty Cycle:**

Continuous

#### **Mounting Configuration:**

Eight 15/32 in. Diameter holes; 4 spaced rectangular pattern 34 in. By 28-1/2 in.; 1 ea at midpoint of rectangular pattern sides

#### **Operating Voltage Characteristic:**

Full

#### **Actuator Voltage:**

440.0 ac

#### **Fuse Current Rating In Amps:**

10.0 and 20.0

#### **Ambient Temp:**

50.0 degrees celsius

#### **Inclosure Feature:**

Dripproof

#### National Electrical Manufacturers Association Standards Design:

Designed per nema std

#### **Amp Size Rating:**

270.0 and 27.0

#### **Switch Functional Positions:**

Start and stop

# NSN 6110-01-168-1620

Motor Controller - Page 2 of 2



**Control Type:** 

Local

**Features Provided:** 

Reversible and circuit protection fuse

Phase:

Three

**Special Features:** 

Additional switch positions: inhaul, outhaul, stream

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A541b0