NSN 6110-01-169-6688

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-169-6688

| Out and Additional transfer |
|--|
| Speed Adjustments: |
| 0 to full speed |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 17.300 inches |
| Overall Height: |
| 8.065 inches |
| Overall Width: |
| 9.360 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Performance Type: |
| Manual |
| Size Designator: |
| 1 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Four 17/32 in. Diameter holes; rectangular pattern; on 6 in. By 14-1/2 in. Centers |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 10.000 |
| Actuator Voltage: |
| 440.0 ac |
| Load Protection Type: |
| Overload and undervoltage |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Switch Functional Positions: |
| Emergency run and start and stop |
| Control Type: |

Local

NSN 6110-01-169-6688

Motor Starter - Page 2 of 2



| Three |
|---------------------|
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A5/1c0 |

Mil-std (military Standard):

Mil-c-2212 spec.

Phase: