

View Online at <https://aerobasegroup.com/nsn/6110-01-170-4765>

**Speed Adjustments:**

0 to full speed

**Hazardous Locations/environmental Protection:**

Dripproof

**Overall Length:**

32.000 inches

**Overall Height:**

8.000 inches

**Overall Width:**

16.000 inches

**Ac Voltage Rating:**

440.0 volts

**Frequency Rating:**

60.0 hertz

**Actuation Method:**

Magnetic

**Performance Type:**

Manual

**Fuse Accommodation Quantity:**

3

**Size Designator:**

0/1

**Duty Cycle:**

Continuous

**Mounting Configuration:**

Six 15/32 in. Diameter holes; 2 rows 3 ea; 14-1/2 in. Cl to cl rows; 15 in. C to c spacing of holes

**Operating Voltage Characteristic:**

Full

**Horsepower Rating:**

5.000 and 10.000

**Actuator Voltage:**

440.0 ac

**Fuse Current Rating In Amps:**

10.0

**Load Protection Type:**

Overload and undervoltage

**Ambient Temp:**

50.0 degrees celsius

**Inclosure Feature:**

Dripproof

**National Electrical Manufacturers Association Standards Design:**

Designed per nema std

**Switch Functional Positions:**

Reset and start and stop

**Control Type:**

Local

**Features Provided:**

Circuit protection fuse

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A541c0

**Mil-std (military Standard):**

Mil-c-2212 spec.