NSN 6110-01-171-3266

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-171-3266

Speed Adjustments:
0 to full speed
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
26.125 inches
Overall Height:
11.500 inches
Overall Width:
24.109 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Manual
Fuse Accommodation Quantity:
1
Size Designator:
5
Duty Cycle:
Continuous
Mounting Configuration:
Six 17/32 in. Diameter holes; rectangular pattern; 2 rows 3 ea on 10-1/4 in. Centers; 24 in. Cl to cl of rows
Operating Voltage Characteristic:
Full
Horsepower Rating:
200.000
Actuator Voltage:
440.0 ac
Fuse Current Rating In Amps:
10.0
Load Protection Type:
Overload
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:
Dripproof
National Flootrical Manufacturers Association Standards Design:

Designed per nema std

NSN 6110-01-171-3266

Motor Starter - Page 2 of 2

Mil-std (military Standard):

Mil-c-2212 spec.



Switch Functional Positions:
Emergency run and reset and start and fast start emergency
Control Type:
Local
Features Provided:
Circuit protection fuse
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A541c0