

View Online at <https://aerobasegroup.com/nsn/6110-01-172-5328>

**Speed Adjustments:**

Two speed

**Hazardous Locations/environmental Protection:**

Dripproof

**Overall Length:**

42.120 inches

**Overall Height:**

9.500 inches

**Overall Width:**

30.100 inches

**Ac Voltage Rating:**

440.0 volts

**Frequency Rating:**

60.0 hertz

**Actuation Method:**

Magnetic

**Performance Type:**

Manual

**Fuse Accommodation Quantity:**

4 and 2

**Size Designator:**

3/2

**Duty Cycle:**

Continuous

**Mounting Configuration:**

Six 17/32 in diameter holes, three top, three bottom, 40 in. By 13-1/4 c to c

**Operating Voltage Characteristic:**

Full

**Horsepower Rating:**

50.000 and 25.000

**Actuator Voltage:**

440.0 ac

**Fuse Current Rating In Amps:**

6.0 and 10.0

**Load Protection Type:**

Overload

**Ambient Temp:**

50.0 degrees celsius

**National Electrical Manufacturers Association Standards Design:**

Designed per nema std

**Switch Functional Positions:**

Emergency run and stop

**Control Type:**

Local

**Features Provided:**

Reversible and circuit protection fuse

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A541b0

**Mil-std (military Standard):**

Mil-c-2212 spec.