# NSN 6110-01-172-5328

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-172-5328

# **Speed Adjustments:**

Two speed

# Hazardous Locations/environmental Protection:

Dripproof

# **Overall Length:**

42.120 inches

#### **Overall Height:**

9.500 inches

#### **Overall Width:**

30.100 inches

#### Ac Voltage Rating:

440.0 volts

# **Frequency Rating:**

60.0 hertz

#### **Actuation Method:**

# Magnetic

Performance Type:

Manual

# **Fuse Accommodation Quantity:**

4 and 2

# Size Designator:

3/2

#### **Duty Cycle:**

Continuous

# **Mounting Configuration:**

Six 17/32 in diameter holes, three top, three bottom, 40 in. By 13-1/4 c to c

# **Operating Voltage Characteristic:**

Full

#### **Horsepower Rating:**

50.000 and 25.000

#### **Actuator Voltage:**

440.0 ac

#### **Fuse Current Rating In Amps:**

6.0 and 10.0

# Load Protection Type:

Overload

# **Ambient Temp:**

50.0 degrees celsius

# National Electrical Manufacturers Association Standards Design:

Designed per nema std

# **Switch Functional Positions:**

Emergency run and stop

# NSN 6110-01-172-5328

Motor Controller - Page 2 of 2

**Control Type:** Local **Features Provided:** Reversible and circuit protection fuse Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A541b0 Mil-std (military Standard): Mil-c-2212 spec.

