## NSN 6110-01-173-4002

Motor Controller - Page 1 of 2

Designed per nema std



View Online at https://aerobasegroup.com/nsn/6110-01-173-4002

Omenal Additional transfer
Speed Adjustments:
0 to full speed
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
34.120 inches
Overall Height:
10.380 inches
Overall Width:
28.100 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Automatic or manual
Fuse Accommodation Quantity:
3
Size Designator:
1
Duty Cycle:
Continuous
Mounting Configuration:
Eight 21/32 in. Diameter holes; retangular pattern; on horizontal plane; spaced 8 in. And 8-1/4 in. C to c, outside 1-5/8 in. Nom
Operating Voltage Characteristic:
Full
Horsepower Rating:
10.000
Actuator Voltage:
115.0 ac
Fuse Current Rating In Amps:
10.0
Load Protection Type:
Overload
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:
Dripproof
National Floctrical Manufacturers Association Standards Design:

## NSN 6110-01-173-4002

Motor Controller - Page 2 of 2



Switch Functional Positions:
Emergency run and start and stop
Control Type:
Local or remote
Features Provided:
Circuit protection fuse
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A541b0

Mil-std (military Standard):

Mil-c-2212 spec.