# NSN 6110-01-173-4002

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-173-4002

### Speed Adjustments:

0 to full speed

#### Hazardous Locations/environmental Protection:

Dripproof

### **Overall Length:**

34.120 inches

#### **Overall Height:**

10.380 inches

#### **Overall Width:**

28.100 inches

#### Ac Voltage Rating:

440.0 volts

#### Frequency Rating:

60.0 hertz

#### **Actuation Method:**

Magnetic

## Performance Type:

Automatic or manual

# Fuse Accommodation Quantity:

3

#### Size Designator:

1

#### Duty Cycle:

Continuous

#### Mounting Configuration:

Eight 21/32 in. Diameter holes; retangular pattern; on horizontal plane; spaced 8 in. And 8-1/4 in. C to c, outside 1-5/8 in. Nom

#### **Operating Voltage Characteristic:**

Full

#### Horsepower Rating:

10.000

#### Actuator Voltage:

115.0 ac

#### **Fuse Current Rating In Amps:**

10.0

#### Load Protection Type:

Overload

#### Ambient Temp:

50.0 degrees celsius

#### **Inclosure Feature:**

Dripproof

#### National Electrical Manufacturers Association Standards Design:

Designed per nema std

# NSN 6110-01-173-4002

Motor Controller - Page 2 of 2



**Switch Functional Positions:** 

Emergency run and start and stop

Control Type:

Local or remote

**Features Provided:** 

Circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541b0

Mil-std (military Standard):

Mil-c-2212 spec.