NSN 6110-01-174-0868

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-174-0868

Speed Adjustments:
0 to full speed
Hazardous Locations/environmental Protection:
Spraytight
Overall Length:
12.125 inches
Overall Height:
9.781 inches
Overall Width:
14.100 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Manual
Fuse Accommodation Quantity:
2
Size Designator:
2
Duty Cycle:
Continuous
Mounting Configuration:
Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 10 in. Centers
Operating Voltage Characteristic:
Full
Horsepower Rating:
5.000
Actuator Voltage:
440.0 ac
Fuse Current Rating In Amps:
10.0
Load Protection Type:
Overload and undervoltage
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:
Spray tight
National Electrical Manufacturers Association Standards Design:

Designed per nema std

NSN 6110-01-174-0868

Motor Starter - Page 2 of 2



Switch Functional Positions:
Emergency run and off and on
Control Type:
Local
Features Provided:
Circuit protection fuse
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A541c0

Mil-std (military Standard):

Mil-c-2212 spec.