

View Online at <https://aerobasegroup.com/nsn/6110-01-174-0868>

Speed Adjustments:

0 to full speed

Hazardous Locations/environmental Protection:

Spraytight

Overall Length:

12.125 inches

Overall Height:

9.781 inches

Overall Width:

14.100 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Manual

Fuse Accommodation Quantity:

2

Size Designator:

2

Duty Cycle:

Continuous

Mounting Configuration:

Four 17/32 in. Diameter holes; rectangular pattern; on 10-1/2 in. By 10 in. Centers

Operating Voltage Characteristic:

Full

Horsepower Rating:

5.000

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Spray tight

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Switch Functional Positions:

Emergency run and off and on

Control Type:

Local

Features Provided:

Circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A541c0

Mil-std (military Standard):

Mil-c-2212 spec.