

View Online at <https://aerobasegroup.com/nsn/6110-01-175-2082>

**Speed Adjustments:**

0 to full speed

**Hazardous Locations/environmental Protection:**

Dripproof

**Overall Length:**

18.125 inches

**Overall Height:**

9.880 inches

**Overall Width:**

12.100 inches

**Ac Voltage Rating:**

440.0 volts

**Frequency Rating:**

60.0 hertz

**Actuation Method:**

Magnetic

**Performance Type:**

Manual

**Fuse Accommodation Quantity:**

2

**Size Designator:**

1

**Duty Cycle:**

Continuous

**Mounting Configuration:**

Four 17/32 in. Diameter holes; rectangular pattern; on 16 in. By 8-1/2 in. Centers

**Operating Voltage Characteristic:**

Full

**Horsepower Rating:**

10.000

**Actuator Voltage:**

440.0 ac

**Fuse Current Rating In Amps:**

10.0

**Load Protection Type:**

Overload and undervoltage

**Ambient Temp:**

50.0 degrees celsius

**Inclosure Feature:**

Dripproof

**National Electrical Manufacturers Association Standards Design:**

Designed per nema std

**Switch Functional Positions:**

Emergency run and start and stop

**Control Type:**

Local

**Features Provided:**

Circuit protection fuse

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541c0

**Mil-std (military Standard):**

Mil-c-2212 spec.