NSN 6110-01-178-5583

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-178-5583

| Speed Adjustments: |
|-------------------------------------------------------------------------------------------------------|
| 0 to full speed |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 29.120 inches |
| Overall Height: |
| 9.560 inches |
| Overall Width: |
| 19.380 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Performance Type: |
| Manual |
| Fuse Accommodation Quantity: |
| 10 |
| Size Designator: |
| 3 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Six 21/32 in. Diameter holes for 5/8 in. Bolts; rectangular pattern, 28-1/8 in. By 14-1/2 in. Centers |
| Operating Voltage Characteristic: |
| Full |
| Actuator Voltage: |
| 115.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 |
| Load Protection Type: |
| Overload |
| Ambient Temp: |
| 50.0 degrees celsius |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Amp Size Rating: |
| 90.0 |
| Switch Functional Positions: |

Emergency stop and remote and reset

NSN 6110-01-178-5583

Motor Controller - Page 2 of 2



| Control Type: |
|-------------------------|
| Local |
| Features Provided: |
| Circuit protection fuse |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A541b0 |

Mil-std (military Standard):

Mil-c-2212 spec.