

View Online at <https://aerobasegroup.com/nsn/6110-01-181-3123>

**Speed Adjustments:**

Two speed

**Hazardous Locations/environmental Protection:**

Spraytight

**Overall Length:**

40.125 inches

**Overall Height:**

11.890 inches

**Overall Width:**

30.109 inches

**Ac Voltage Rating:**

440.0 volts

**Frequency Rating:**

60.0 hertz

**Actuation Method:**

Magnetic

**Performance Type:**

Manual

**Fuse Accommodation Quantity:**

8

**Size Designator:**

5/5

**Duty Cycle:**

Continuous

**Mounting Configuration:**

Eight 21/32 in. Diameter holes; 2 parallel rows of 4 ea; c to c spacing from end of row, 8-3/4, 9 and 8-3/4 in; 38 in. Cl to cl of rows

**Operating Voltage Characteristic:**

Full

**Actuator Voltage:**

440.0 ac

**Fuse Current Rating In Amps:**

10.0

**Ambient Temp:**

50.0 degrees celsius

**Inclosure Feature:**

Spray tight

**National Electrical Manufacturers Association Standards Design:**

Designed per nema std

**Amp Size Rating:**

270.0

**Control Type:**

Local

**Features Provided:**

Circuit protection fuse

**Phase:**

Three

**Special Features:**

Heater application; 50kw and 103.8kw positions provided

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A541b0

**Mil-std (military Standard):**

Mil-c-2212 spec.