

View Online at <https://aerobasegroup.com/nsn/6110-01-181-3123>

Speed Adjustments:

Two speed

Hazardous Locations/environmental Protection:

Spraytight

Overall Length:

40.125 inches

Overall Height:

11.890 inches

Overall Width:

30.109 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Manual

Fuse Accommodation Quantity:

8

Size Designator:

5/5

Duty Cycle:

Continuous

Mounting Configuration:

Eight 21/32 in. Diameter holes; 2 parallel rows of 4 ea; c to c spacing from end of row, 8-3/4, 9 and 8-3/4 in; 38 in. Cl to cl of rows

Operating Voltage Characteristic:

Full

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

10.0

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Spray tight

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Amp Size Rating:

270.0

Control Type:

Local

Features Provided:

Circuit protection fuse

Phase:

Three

Special Features:

Heater application; 50kw and 103.8kw positions provided

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A541b0

Mil-std (military Standard):

Mil-c-2212 spec.