NSN 6110-01-181-8783

Motor Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6110-01-181-8783

Hazardous Locations/environmental Protection:
Dripproof
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Automatic
Size Designator:
1
Duty Cycle:
Continuous
Operating Voltage Characteristic:
Full
Horsepower Rating:
10.000
Actuator Voltage:
440.0 ac
Ambient Temp:
Ambient Temp: 50.0 degrees celsius
50.0 degrees celsius
50.0 degrees celsius Inclosure Feature:
50.0 degrees celsius Inclosure Feature: Dripproof
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design:
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type:
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase:
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz:
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life:
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure:
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure: Demilitarization: