

View Online at <https://aerobasegroup.com/nsn/6110-01-187-5237>

**Speed Adjustments:**

Single speed

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

29.125 inches

**Overall Height:**

10.100 inches

**Overall Width:**

19.400 inches

**Ac Voltage Rating:**

440.0 volts

**Frequency Rating:**

60.0 hertz

**Actuation Method:**

Magnetic

**Performance Type:**

Manual

**Fuse Accommodation Quantity:**

4

**Size Designator:**

1

**Duty Cycle:**

Intermittent

**Mounting Configuration:**

Six flange type tabs with 21/32 in. Diameter hole; 2 rows 3 ea spaced 7-1/4 c to c; 30 in. Cl to cl rows

**Operating Voltage Characteristic:**

Full

**Horsepower Rating:**

5.000

**Actuator Voltage:**

110.0 ac

**Fuse Current Rating In Amps:**

10.0

**Load Protection Type:**

Overload and undervoltage and undervoltage release

**Ambient Temp:**

50.0 degrees celsius

**Inclosure Feature:**

Watertight

**National Electrical Manufacturers Association Standards Design:**

Designed per nema std

**Switch Functional Positions:**

Emergency run

**Control Type:**

Local or remote

**Features Provided:**

Reversible and circuit protection fuse

**Phase:**

Three

**Special Features:**

Additional switch functional positions: port, starboard

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541b0

**Mil-std (military Standard):**

Mil-c-2212 spec.