

View Online at <https://aerobasegroup.com/nsn/6110-01-187-5237>

Speed Adjustments:

Single speed

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

29.125 inches

Overall Height:

10.100 inches

Overall Width:

19.400 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Manual

Fuse Accommodation Quantity:

4

Size Designator:

1

Duty Cycle:

Intermittent

Mounting Configuration:

Six flange type tabs with 21/32 in. Diameter hole; 2 rows 3 ea spaced 7-1/4 c to c; 30 in. Cl to cl rows

Operating Voltage Characteristic:

Full

Horsepower Rating:

5.000

Actuator Voltage:

110.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage and undervoltage release

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Watertight

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Switch Functional Positions:

Emergency run

Control Type:

Local or remote

Features Provided:

Reversible and circuit protection fuse

Phase:

Three

Special Features:

Additional switch functional positions: port, starboard

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541b0

Mil-std (military Standard):

Mil-c-2212 spec.