

View Online at <https://aerobasegroup.com/nsn/6110-01-188-0301>

Speed Adjustments:

Two speed

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

50.000 inches

Overall Height:

16.000 inches

Overall Width:

36.000 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Manual

Fuse Accommodation Quantity:

6

Size Designator:

6/4

Duty Cycle:

Continuous

Mounting Configuration:

Eight 21/32 in. Diameter holes; rectangular pattern; two rows 3 ea; 33 in. Cl to cl rows; 23-1/2 in. C to c holes; 2 holes centered between rows; 1 ea end

Operating Voltage Characteristic:

Full

Horsepower Rating:

400.000 and 100.000

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Dripproof

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Amp Size Rating:

540.0 and 135.0

Switch Functional Positions:

Emergency and high speed and low speed and manual and reset and stop

Control Type:

Local

Features Provided:

Circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541b0

Mil-std (military Standard):

Mil-c-2212 spec.