

View Online at <https://aerobasegroup.com/nsn/6110-01-191-5059>

Speed Adjustments:

Two speed

Hazardous Locations/environmental Protection:

Spraytight

Overall Length:

32.125 inches

Overall Height:

9.380 inches

Overall Width:

22.108 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Manual

Fuse Accommodation Quantity:

2

Size Designator:

4/3

Duty Cycle:

Continuous

Mounting Configuration:

Six 17/32 in. Diameter holes; rectangular pattern; 2 rows 3 ea holes spaced 9-1/4 in. C to c; 30 in. Cl to cl rows

Operating Voltage Characteristic:

Full

Horsepower Rating:

100.000

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Spray tight

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Switch Functional Positions:

Emergency run and fast and slow and standby

Control Type:

Local

Features Provided:

Circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A541b0