

View Online at <https://aerobasegroup.com/nsn/6110-01-196-2141>

**Speed Adjustments:**

Two speed

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

35.120 inches

**Overall Height:**

9.100 inches

**Overall Width:**

27.400 inches

**Ac Voltage Rating:**

440.0 volts

**Frequency Rating:**

60.0 hertz

**Actuation Method:**

Magnetic

**Performance Type:**

Manual

**Fuse Accommodation Quantity:**

4

**Size Designator:**

2

**Duty Cycle:**

Continuous

**Mounting Configuration:**

Six 21/32 in. Holes; rectangular pattern; two rows of 3 each spaced 11.250 in. C to c from end of row; 34 in. Cl to cl rows

**Operating Voltage Characteristic:**

Full

**Horsepower Rating:**

15.000

**Actuator Voltage:**

110.0 ac and 115.0 ac

**Fuse Current Rating In Amps:**

10.0

**Load Protection Type:**

Overload and undervoltage

**Ambient Temp:**

50.0 degrees celsius

**Inclosure Feature:**

Watertight

**National Electrical Manufacturers Association Standards Design:**

Designed per nema std

**Switch Functional Positions:**

Emergency run and fast and slow

**Control Type:**

Local or remote

**Features Provided:**

Reversible and circuit protection fuse

**Phase:**

Three

**Special Features:**

Port hoist controller

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541b0