

View Online at <https://aerobasegroup.com/nsn/6110-01-196-2141>

Speed Adjustments:

Two speed

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

35.120 inches

Overall Height:

9.100 inches

Overall Width:

27.400 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Manual

Fuse Accommodation Quantity:

4

Size Designator:

2

Duty Cycle:

Continuous

Mounting Configuration:

Six 21/32 in. Holes; rectangular pattern; two rows of 3 each spaced 11.250 in. C to c from end of row; 34 in. Cl to cl rows

Operating Voltage Characteristic:

Full

Horsepower Rating:

15.000

Actuator Voltage:

110.0 ac and 115.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Watertight

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Switch Functional Positions:

Emergency run and fast and slow

Control Type:

Local or remote

Features Provided:

Reversible and circuit protection fuse

Phase:

Three

Special Features:

Port hoist controller

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541b0