NSN 6110-01-196-2142

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-196-2142

Speed Adjustments:
Single speed
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
54.000 inches
Overall Height:
20.000 inches
Overall Width:
35.750 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Automatic
Size Designator:
5
Duty Cycle:
Continuous
Mounting Configuration:
Eight 15/32 in. Diameter holes, 2 rows of 3 each spaced 26.25 in. C to c; 33.75 in. Cl to cl rows; 2 holes centered between ends of rows
Operating Voltage Characteristic:
Full
Actuator Voltage:
120.0 ac
Load Protection Type:
Overload
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:
Dripproof
National Electrical Manufacturers Association Standards Design:
Designed per nema std
Control Type:
Local or remote
Phase:
Three
Special Features:

Wye delta motor closed transition design, provided with timing and cut out relays for motor protection

NSN 6110-01-196-2142

Motor Starter - Page 2 of 2



Frequency I	In Hertz:	
-------------	-----------	--

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0