NSN 6110-01-212-0578

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-212-0578

| Hazardous Locations/environmental Protection: |
|---|
| |
| Dripproof Overall Learnth |
| Overall Length: |
| 8.000 inches |
| Overall Height: |
| 18.000 inches |
| Overall Width: |
| 16.000 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Size Designator: |
| 0 |
| Duty Cycle: |
| Continuous |
| Operating Voltage Characteristic: |
| Full |
| Actuator Voltage: |
| 440.0 ac |
| Load Protection Type: |
| Overload |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Switch Functional Positions: |
| Emergency run and reset and start and stop |
| Control Type: |
| Local or remote |
| Phase: |
| Three |
| Special Features: |
| Actuation method: magnetic or manual |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 6110-01-212-0578

Motor Controller - Page 2 of 2



| _ | | | | | |
|----|-----|---------|-----|---|--|
| 11 | em) | tor | 172 | n | |
| | | | | | |

No

Fiig:

A541b0