---



| Motor Controller - Page 1 of 2                                  |
|---|
| View Online at https://aerobasegroup.com/nsn/6110-01-213-3179   |
| Hazardous Locations/environmental Protection:                   |
| Dripproof   |
| Overall Length:   |
| 10.000 inches   |
| Overall Height:   |
| 28.000 inches   |
| Overall Width:  |
| 8.875 inches  |
| Ac Voltage Rating:  |
| 440.0 volts   |
| Frequency Rating:   |
| 60.0 hertz  |
| Size Designator:  |
| 0   |
| Duty Cycle:   |
| Continuous  |
| Operating Voltage Characteristic:                               |
| Full  |
| Actuator Voltage:   |
| 440.0 ac  |
| Load Protection Type:   |
| Overload  |
| Ambient Temp:   |
| 50.0 degrees celsius  |
| Inclosure Feature:  |
| Dripproof and fully enclosed                                    |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std   |
| Switch Functional Positions:                                    |
| Emergency run and reset and start and stop                      |
| Control Type:   |
| Local or remote   |
| Phase:  |
| Three   |
| Special Features:   |
| Actuation method: magnetic or manual                            |
| Frequency In Hertz:   |
| 60.0  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

## NSN 6110-01-213-3179

Motor Controller - Page 2 of 2

Demilitarization:

No

Fiig:

A541b0

