NSN 6110-01-213-4972

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-213-4972

| Hazardous Locations/environmental Protection: |
|---|
| Dripproof |
| Overall Length: |
| 6.668 inches |
| Overall Height: |
| 15.560 inches |
| Overall Width: |
| 8.240 inches |
| Ac Voltage Rating: |
| 208.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Performance Type: |
| Semiautomatic |
| Size Designator: |
| 1 |
| Duty Cycle: |
| Continuous |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 10.000 |
| Actuator Voltage: |
| 208.0 ac |
| Load Protection Type: |
| Undervoltage release |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Switch Functional Positions: |
| Reset and start and stop |
| Control Type: |
| Local |
| Phase: |
| Three |
| Frequency In Hertz: |

60.0

NSN 6110-01-213-4972

Motor Controller - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A541b0 | |

Mil-std (military Standard):

Mil-c-2212 spec.

Shelf Life: