NSN 6110-01-219-3808

Motor Starter - Page 1 of 2

Speed Adjustments:



View Online at https://aerobasegroup.com/nsn/6110-01-219-3808

Single speed
Hazardous Locations/environmental Protection:
Spraytight
Overall Length:
8.531 inches
Overall Height:
9.000 inches
Overall Width:
6.625 inches
Ac Voltage Rating:
440.0 volts
Unable To Decode:
Unable to decode and unable to decode
Frequency Rating:
60.0 hertz
Actuation Method:
Manual
Performance Type:
Manual
Duty Cycle:
Continuous
Operating Voltage Characteristic:
Full
Horsepower Rating:
0.500 and 1.500
Load Protection Type:
Overload and undervoltage release effect
Ambient Temp:
50.0 degrees celsius
National Electrical Manufacturers Association Standards Design:
Not designed per nema std
Switch Functional Positions:
Emergency run and reset and start and stop
Control Type:
Local
Criticality Code Justification:
Zzzy
Phase:
Single and three
Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

NSN 6110-01-219-3808

Motor Starter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A541c0