## NSN 6110-01-221-1974

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-221-1974

| Speed Adjustments:  |
|---|
| Two speed   |
| Overall Length:   |
| 24.000 inches   |
| Overall Height:   |
| 8.000 inches  |
| Overall Width:  |
| 16.000 inches   |
| Ac Voltage Rating:  |
| 440.0 volts   |
| Frequency Rating:   |
| 60.0 hertz  |
| Actuation Method:   |
| Magnetic  |
| Fuse Accommodation Quantity:  |
| 2   |
| Size Designator:  |
| 2/0   |
| Duty Cycle:   |
| Continuous  |
| Mounting Configuration:   |
| Four 15/32 in. Diameter mtg holes on 22.000 in. By 14.500 in. Mtg ctr |
| Operating Voltage Characteristic:                                     |
| Full  |
| Actuator Voltage:   |
| 440.0 ac  |
| Fuse Current Rating In Amps:  |
| 10.0  |
| Load Protection Type:   |
| Overload  |
| Ambient Temp:   |
| 50.0 degrees celsius  |
| Inclosure Feature:  |
| Dripproof   |
| National Electrical Manufacturers Association Standards Design:       |
| Designed per nema std   |
| Switch Functional Positions:  |
| Stop and fast and slow and run  |
| Control Type:   |
| Local or remote   |
| Features Provided:  |

Circuit protection fuse

## NSN 6110-01-221-1974

Motor Controller - Page 2 of 2



| Three               |
|---------------------|
| Frequency In Hertz: |
| 60.0                |
| Shelf Life:         |
| N/a                 |
| Unit Of Measure:    |
|                     |
| Demilitarization:   |
| No                  |
| Fiig:               |
| A541b0              |

Mil-std (military Standard):

Mil-c-2212 spec.

Phase: