NSN 6110-01-222-9304

Motor Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6110-01-222-9304

Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
10.000 inches
Overall Height:
24.000 inches
Overall Width:
22.000 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Size Designator:
1
Duty Cycle:
Continuous
Operating Voltage Characteristic:
Full
Actuator Voltage:
Actuator Voltage: 440.0 ac
440.0 ac
440.0 ac Ambient Temp:
440.0 ac Ambient Temp: 50.0 degrees celsius
440.0 ac Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design:
440.0 ac Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std
440.0 ac Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type:
440.0 ac Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote
440.0 ac Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase:
440.0 ac Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three
440.0 ac Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz:
440.0 ac Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0
440.0 ac Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life:
Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a
Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a
Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure:
Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure: Demilitarization: