NSN 6110-01-237-2547

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-237-2547

| Hazardous Locations/environmental Protection: |
|---|
| Dripproof |
| Overall Length: |
| 13.000 inches |
| Overall Height: |
| 36.000 inches |
| Overall Width: |
| 24.000 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Fuse Accommodation Quantity: |
| 4 |
| Size Designator: |
| 2 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Six 5/32 in. Diameter mtg holes on 11-1/4 in. By 17 in. Mtg ctr |
| Operating Voltage Characteristic: |
| Full |
| Actuator Voltage: |
| 440.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 |
| Load Protection Type: |
| Overload |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Control Type: |
| Local or remote |
| Features Provided: |
| Circuit protection fuse |
| Phase: |

Three

NSN 6110-01-237-2547

Motor Starter - Page 2 of 2



| Frequency In | Hertz: |
|--------------|--------|
|--------------|--------|

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0