NSN 6110-01-246-9932

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-246-9932

| Hazardous Locations/environmental Protection: |
|--|
| Spraytight |
| Overall Length: |
| 26.120 inches |
| Overall Width: |
| 18.100 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Fuse Accommodation Quantity: |
| 6 |
| Duty Cycle: |
| Continuous |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 100.000 |
| Fuse Current Rating In Amps: |
| 10.0 |
| Load Protection Type: |
| Overload |
| Ambient Temp: |
| 50.0 degrees celsius |
| Control Type: |
| Local |
| Features Provided: |
| Circuit protection fuse |
| Criticality Code Justification: |
| Zzzy |
| Phase: |
| Three |
| Specification Data: |
| 81349-mil-c-2212 government specification |
| Reference Number Differentiating Characteristics: |
| Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 6110-01-246-9932

Motor Controller - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A541b0