NSN 6110-01-249-5034

Motor Controller - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6110-01-249-5034

Speed Adjustments:
Two speed
Overall Length:
16.000 inches
Overall Height:
24.000 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Fuse Accommodation Quantity:
4 and 4
Size Designator:
2
Horsepower Rating:
5.000 and 25.000
Actuator Voltage:
110.0 ac
Fuse Current Rating In Amps:
Fuse Current Rating In Amps: 5.0 and 15.0
5.0 and 15.0
5.0 and 15.0 Load Protection Type:
5.0 and 15.0 Load Protection Type: Overload
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design:
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions:
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop Features Provided:
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop Features Provided: Circuit protection fuse
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop Features Provided: Circuit protection fuse Phase:
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop Features Provided: Circuit protection fuse Phase: Three
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop Features Provided: Circuit protection fuse Phase: Three Shelf Life:
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop Features Provided: Circuit protection fuse Phase: Three Shelf Life: N/a Unit Of Measure:
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop Features Provided: Circuit protection fuse Phase: Three Shelf Life: N/a
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop Features Provided: Circuit protection fuse Phase: Three Shelf Life: N/a Unit Of Measure:
5.0 and 15.0 Load Protection Type: Overload National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Reset and fast and slow and stop Features Provided: Circuit protection fuse Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: