## NSN 6110-01-259-4214

Motor Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6110-01-259-4214

Hazardous Locations/environmental Protection:
Dripproof
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Fuse Accommodation Quantity:
2
Size Designator:
4
Duty Cycle:
Continuous
Operating Voltage Characteristic:
Full
Horsepower Rating:
75.000
Fuse Current Rating In Amps:
10.0
Ambient Temp:
Ambient Temp: 50.0 degrees celsius
50.0 degrees celsius
50.0 degrees celsius Inclosure Feature:
50.0 degrees celsius  Inclosure Feature:  Dripproof
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design:
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type:
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Features Provided:
50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Features Provided: Circuit protection fuse
50.0 degrees celsius  Inclosure Feature: Dripproof  National Electrical Manufacturers Association Standards Design: Designed per nema std  Control Type: Local or remote  Features Provided: Circuit protection fuse  Phase:
50.0 degrees celsius  Inclosure Feature: Dripproof  National Electrical Manufacturers Association Standards Design: Designed per nema std  Control Type: Local or remote  Features Provided: Circuit protection fuse  Phase: Three
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Features Provided: Circuit protection fuse Phase: Three Shelf Life:
50.0 degrees celsius  Inclosure Feature: Dripproof  National Electrical Manufacturers Association Standards Design: Designed per nema std  Control Type: Local or remote Features Provided: Circuit protection fuse  Phase: Three Shelf Life: N/a
50.0 degrees celsius  Inclosure Feature: Dripproof  National Electrical Manufacturers Association Standards Design: Designed per nema std  Control Type: Local or remote Features Provided: Circuit protection fuse  Phase: Three Shelf Life: N/a
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Features Provided: Circuit protection fuse Phase: Three Shelf Life: N/a Unit Of Measure:
Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Features Provided: Circuit protection fuse Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: