NSN 6110-01-281-8858

Motor Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6110-01-281-8858

Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
15.000 inches
Overall Height:
50.000 inches
Overall Width:
36.000 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Size Designator:
4
Duty Cycle:
Continuous
Actuator Voltage:
115.0 ac
Load Protection Type:
Load Protection Type: Overload
Overload
Overload Ambient Temp:
Overload Ambient Temp: 50.0 degrees celsius
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design:
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type:
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase:
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz:
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life:
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure:
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure: Demilitarization: