NSN 6110-01-286-5044

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-286-5044

| Speed Adjustments: |
|---|
| Single speed |
| Overall Length: |
| 34.000 inches |
| Overall Height: |
| 12.000 inches |
| Overall Width: |
| 18.000 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| End Application: |
| Low pressure blower |
| Performance Type: |
| Manual |
| Fuse Accommodation Quantity: |
| 2 |
| Size Designator: |
| 5 |
| Duty Cycle: |
| Continuous |
| Horsepower Rating: |
| 200.000 |
| Fuse Current Rating In Amps: |
| 10.0 |
| Load Protection Type: |
| Overload and undervoltage |
| Ambient Temp: |
| 50.0 degrees celsius |
| |
| Inclosure Feature: |
| Dripproof |
| |
| Dripproof |
| Dripproof National Electrical Manufacturers Association Standards Design: |
| Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std |
| Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: |
| Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Stop and start and reset |
| Dripproof National Electrical Manufacturers Association Standards Design: Designed per nema std Switch Functional Positions: Stop and start and reset Features Provided: |

NSN 6110-01-286-5044

Motor Starter - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0