Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-299-2598

| Ac V | oltage Rating: |
|-------|-------------------------------------------------------------|
| 440. |) volts |
| Freq | uency Rating: |
| 60.0 | hertz |
| Actu | ation Method: |
| Mag | netic |
| Fuse | Accommodation Quantity: |
| 3 an | 12 |
| Size | Designator: |
| 5 | |
| Duty | Cycle: |
| Cont | inuous |
| Ope | rating Voltage Characteristic: |
| Full | |
| Hors | epower Rating: |
| 200. | 000 |
| Actu | ator Voltage: |
| 115. |) ac |
| Fuse | Current Rating In Amps: |
| 30.0 | and 10.0 |
| Load | I Protection Type: |
| Unde | prvoltage |
| Inclo | sure Feature: |
| Dripp | proof |
| Natio | onal Electrical Manufacturers Association Standards Design: |
| Desi | gned per nema std |
| Amp | Size Rating: |
| 227. |) |
| Con | rol Type: |
| Loca | I or remote |
| Feat | ures Provided: |
| Circu | it protection fuse |
| Phas | se: |
| Thre | e |
| Freq | uency In Hertz: |
| 60.0 | |
| Shel | f Life: |
| N/a | |
| Unit | Of Measure: |
| | |
| Dem | ilitarization: |
| No | |

NSN 6110-01-299-2598

Motor Starter - Page 2 of 2

Fiig: A541c0

