NSN 6110-01-299-2602

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-299-2602

| Hazardous Locations/environmental Protection: |
|---|
| Dripproof |
| Overall Height: |
| 12.000 inches |
| Overall Width: |
| 16.000 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Fuse Accommodation Quantity: |
| 2 and 2 |
| Size Designator: |
| 1 |
| Duty Cycle: |
| Continuous |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 2.000 |
| Actuator Voltage: |
| 110.0 ac |
| Fuse Current Rating In Amps: |
| 1.0 and 2.0 |
| Load Protection Type: |
| Undervoltage |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Amp Size Rating: |
| 2.9 |
| Control Type: |
| Local or remote |
| Features Provided: |
| Circuit protection fuse |
| Phase: |
| Three |
| Frequency In Hertz: |

60.0

NSN 6110-01-299-2602

Motor Starter - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0