## NSN 6110-01-306-7250

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-306-7250

## Speed Adjustments:

Two speed

#### Hazardous Locations/environmental Protection:

Watertight

## **Overall Length:**

33.120 inches

#### **Overall Width:**

23.380 inches

### Ac Voltage Rating:

440.0 volts

#### **Frequency Rating:**

60.0 hertz

#### **Actuation Method:**

Magnetic

## **End Application:**

Bridge drive

#### **Fuse Accommodation Quantity:**

4

#### Duty Cycle:

Continuous

#### Mounting Configuration:

Six 21/32 diameter holes for 5/8 mtg bolts

#### Horsepower Rating:

10.000

#### **Fuse Current Rating In Amps:**

10.0

#### Load Protection Type:

Overload and undervoltage

#### Ambient Temp:

50.0 degrees celsius

#### **Inclosure Feature:**

Watertight

#### National Electrical Manufacturers Association Standards Design:

Not designed per nema std

#### **Switch Functional Positions:**

Slow and fast

## **Features Provided:**

Circuit protection fuse

## Phase:

Three

## Shelf Life:

N/a

# NSN 6110-01-306-7250

Motor Controller - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A541b0

